

Product Specification



CCFA-829

Multiband Combiner

- Covers 700,850,1900,AWS1 & AWS3 Bands
- Compact Size with Low Loss
- Use With FORCE™ Neutral Host Combiner
- High Isolation / PIM Rated

Electrical Specifications

PASSBAND

COMMON PORT	698 - 2180 MHz
700 BAND PORT	698 - 787 MHz
850 BAND PORT	824 - 894 MHz
1900 BAND PORT	1850 - 1995 MHz
AWS1 BAND PORT	1715-1735 MHz & 2115-2135 MHz
AWS3 BAND PORT	1770 – 1780 MHz & 2170-2180 MHz
INSERTION LOSS RETURN LOSS	0.5 dB Max, 0.3 dB Typ. 20 dB Min.
ISOLATION	30 dB Min, 50 dB Typ.
POWER HANDLING	100W Avg. / 500 W Peak
PASSIVE INTERMODS	-156 dBc


Environmental Specifications

OPERATING TEMPERATURE	-40° to +65°C Operating
ENVIRONMENTAL	Per IP-65 (IP-67 Optional)
ENVIRONMENTAL RATING	ETSI EN 300 019 Class 4.1, RoHS
LIGHTNING PROTECTION	EN / IEC 61000 4-5, Level 4
ALTITUDE	3,000m Max. (10,000 Ft) 10 ⁷
MEAN TIME BETWEEN FAILURES	Hrs. Min

Product Specification

Mechanical Specifications

CONNECTORS	4.3/10.0 Female
SIZE	300 x 183 x 53.4mm (11.81" x 7.20" x 2.10")
WEIGHT	Excluding Connectors Approx. 5.5 kg (12 lbs.)



OUTLINE DRAWING